

Female Thread Hose Couplings **Gunmetal Grooved Tail**

Scope of Use / Specification Sheet

Couplings are available in both gunmetal and aluminium and are available in threads for all states requirements including BI, Storz and NHT. These couplings are used to connect to layflat hose enabling you to connect to hydrant valves. Tail sizes range from 38mm to 65mm in both serrated and grooved.



Parts List	
Order Code	Description
FS5106	38mm BSP Nut x 38mm Grooved Hose Tail
FS5053	65mm CFA Nut x 38mm Grooved Hose Tail
FS5054	65mm CFA Nut x 65mm Grooved Hose Tail
FS5087	65mm FBT Nut x 38mm Grooved Hose Tail
FS5090	65mm FBT Nut x 50mm Grooved Hose Tail
FS5091	65mm FBT Nut x 65mm Grooved Hose Tail
FS5120	65mm QRT Nut x 38mm Grooved Hose Tail
FS5122	65mm QRT Nut x 50mm Grooved Hose Tail
FS5123	65mm QRT Nut x 65mm Grooved Hose Tail

Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three - Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500. For further Scope of Use, please visit matthewsfirealarm.com.au/brochures

